



Automatic Switch Mode Battery Charger

Model
SEC-1215UL
15 Amps
12 VDC

Design Features

- Switch mode technology for high efficiency, lightweight and quiet operation
- Automatic operation for ALL Lead Acid Batteries: Flooded, AGM or Gel Cell
- Can charge 3 banks of batteries simultaneously, no isolator necessary
- Can be used as a power supply or DC UPS when used in conjunction with a battery
- User Configurable AC Input voltage 120 or 230 VAC, 50 / 60 Hz
- User Selectable (by DIP Switch) for 2 or 3 stage, rapid and safe charging of stand-alone and loaded Lead Acid Batteries
- Ammeter & LED power status indicator
- Protections: Short circuit, overload, reverse battery polarity
- Convection cooled

2 YEAR LIMITED WARRANTY



		MODEL NO.	SEC-1215UL
INPUT	NOMINAL INPUT VOLTAGE AND FREQUENCY		120 VAC, 50 / 60 Hz (Default) ; 230 VAC, 50 / 60Hz (Internal jumper setting)
	AC INPUT CONNECTION		Attached Power Cord: 6 ft length ; 3 x 18AWG wire size ; NEMA5-15P Plug
OUTPUT	CHARGING CURRENT		15A
	CHARGING STAGES		3 Stages (DIP Switch setting - Default): Bulk, Absorption and Float 2 Stages (DIP Switch setting): Bulk and Float
	CHARGING VOLTAGES		Absorption: 14.4 VDC (Default) ; 14.0 VDC (DIP Switch setting) ; Disable (DIP Switch setting)
	NO. OF CHARGING BANKS		3
MONITORING	OUTPUT CONNECTIONS		Tubular Hole with Set Screw ; Hole Diameter: 4 mm / 0.16 in
	LED DISPLAY		Red LED: Output is available
	ANALOGUE METER		Ammeter: 0 to 15A
COOLING	TYPE OF COOLING		Convection cooled (No fan)
PROTECTIONS	OUTPUT SHORT CIRCUIT		No output voltage. Auto reset on removal of short
	INPUT OVERLOAD		4A input side fuse will blow (120 VAC input)
	OUTPUT OVERLOAD		Electronic current limit at 15A
	REVERSE POLARITY ON OUTPUT SIDE		20A output side fuse will blow
FUSES	INTERNAL AC INPUT SIDE FUSE (120 VAC OPERATION)		4A, 250V; Size 5mm x 20mm; Time Delay Type Mfr.: Littelfuse 0218004 or equivalent
	INTERNAL AC INPUT SIDE FUSE (230 VAC OPERATION)		2A, 250V; Size 5mm x 20mm; Time Delay Type Mfr.: Littelfuse 0218002 or equivalent
	INTERNAL DC OUTPUT SIDE FUSE		32V, 20A; Automotive Blade Type; Fast Acting Mfr.: Littelfuse 0287020 or equivalent
ENVIRONMENT	OPERATING TEMPERATURE RANGE		-20°C to +40°C / -4°F to +104°F
	STORAGE TEMPERATURE		-30°C to +70°C / -22°F to +158°F
	RELATIVE HUMIDITY		Up to 90%, non condensing
	OPERATING CONDITIONS		Indoor, ventilated, cool and dust free
COMPLIANCE	SAFETY		Intertek-ETL Listed as follows: • Conforms to ANSI/UL Standard 1564 • Certified to CAN/CSA STD. C22.2 No. 107.2
	EMI		FCC Part 15(B), Class B
DIMENSIONS	L x W x H		218 x 214 x 83 mm / 8.6 x 8.4 x 3.3 in
	WEIGHT		2.2 kg / 4.8 lbs

NOTES: 1. DC voltages are based on battery temperature of 86° F / 26.7°C
2. Specifications are subject to change without notice

12001-SEC-1215UL-0119